



CLASSIC Series | TCM 3100 Coriolis Mass Flow Meter

FEATURES

- Robust, no moving parts for long life
- Custom flow connectors & installation lengths
- Excellent repeatability ($\pm 0.05\%$ of flow rate)
- High pressure option: 345 bar [5,000 psi]¹⁾

BENEFITS

- ▶ Increased productivity, lower maintenance
- ▶ Lower installation cost
- ▶ Increased product quality
- ▶ Broad applications: dosing, paint, chemical injection

FLOW RATE

Mass Flow Rate (max.): 3,100 kg/h [114 lb/min]
 Volumetric Flow Rate (max.): 3,100 l/h
 [13.65 gpm, 468 oi bbl/d (US)]
 Nominal Meter Size: DN6 [1/4"]

PRESSURE RATING

200 bar [2,900 psi]
 (option: up to 345 bar [5,000 psi])¹⁾

ACCURACY (LIQUIDS)²⁾

Basic Accuracy (Mass Flow)³⁾: $\pm 0.3\%$ (option: up to $\pm 0.1\%$) of flow rate
 Repeatability (Mass Flow): $\pm 0.05\%$ of flow rate
 Basic Accuracy (Volume Flow)³⁾: $\pm 0.3\%$ (option: up to $\pm 0.15\%$) of flow rate
 Repeatability (Volume Flow): $\pm 0.05\%$ of flow rate
 Zero Stability: $\pm 0.01\%$ of full scale

ACCURACY (GASES)

Basic Accuracy (Mass Flow)³⁾: $\pm 1\%$ (option: up to $\pm 0.5\%$) of flow rate
 Repeatability (Mass Flow): $\pm 0.25\%$ of flow rate

DENSITY


Density Range: up to 2,500 kg/m³ [2.5 g/cm³]
 Density Accuracy³⁾: ± 1.0 kg/m³ [± 0.001 g/cm³]
 Density Repeatability: ± 0.5 kg/m³ [± 0.0005 g/cm³]

TEMPERATURE

Process Temperature Range: -40 °C ... +100 °C [-40 °F ... +212 °F]
 Option: -60 °C ... +200 °C [-76 °F ... +392 °F]
 Temperature Accuracy: ± 1 °C $\pm 0.5\%$ of reading
 [± 1.8 °F $\pm 0.5\%$ of reading]
 Temperature Repeatability: ± 0.2 °C [± 0.36 °F]

MATERIALS (WETTED PARTS)

Tubes: 1.4404 [AISI 316L]
 Case: 1.4404 [AISI 316L]
 Flow Splitter: 1.4404 [AISI 316L]
 Brazing Alloy: BNi-2




¹⁾ The 200 bar standard pressure rating is per ASME. The 345 bar option is non-ASME rated.

²⁾ Stated flow accuracy combines the effects of repeatability, linearity and hysteresis.

³⁾ The specifications refer to standard conditions (for further information see TCM CLASSIC series manual).



CLASSIC Series | TCM 3100 Coriolis Mass Flow Meter



METER DIMENSIONS⁴⁾ AND WEIGHTS

A) Compact Version

Weight: 11.6 kg [25.6 lb]

With meter mount in aluminum diecast housing

B) Remote Version

Weight: 12.9 kg [28.4 lb]

With junction box and remote field mount

Standard Process Connection

G $\frac{1}{2}$ " thread (others on request)


EX-CERTIFICATIONS

ATEX	Zone 1:	Group IIC or IIB, T2...T4
	Zone 2:	II 3G Ex nA IIC T2...T4 Gc
IECEX	Zone 1:	Group IIC or IIB, T2...T4
cCSAus ⁷⁾	Class 1, Division 1:	Group A, B, C, D or C, D, T2...T4
ATEX + IECEx + cCSAus triple approval ^{7) 8)}	Zone 1:	Group IIC or IIB, T2...T4
	Class 1, Division 1:	Group A, B, C, D or C, D, T2...T4
EAC (TR-CU) ⁷⁾		Group IIC or IIB, T2 ... T4

PANEL MOUNT⁵⁾



REMOTE MOUNT⁶⁾



ELECTRONICS

Power Supply: 24 V DC \pm 20 % or 90 ... 264 V AC
 Outputs: Analog, Frequency, Pulse, Status
 Interfaces: RS485 RTU (Modbus), HART[®]
 Cable Gland: M20 | $\frac{1}{2}$ " NPT

⁴⁾ Drawing of the Meter Dimensions reflects one standard connection, other connections on request (Installation length can vary depending on selected connection).

⁵⁾ Weight: 0.4 kg [0.88 lb].

⁶⁾ Weight with aluminum diecast housing: 3.8 kg [8.4 lb] with 3 m cable, Weight with 1.4404 [AISI 316L] housing: 6.15 kg [13.56 lb].

⁷⁾ For Ex1, Ex3, EAC (TR-CU) the electronic is only available in aluminum housing.

⁸⁾ Only with remote electronics.

www.tricorflow.com

N & S AMERICA
 AW-Lake Company
 2440 W. Corporate Preserve Dr. #600
 Oak Creek WI 53154 | USA
 +1 414 574 4300

ASIA PACIFIC & MIDDLE EAST
 KEM Küppers Elektromechanik GmbH
 1 Magazine Road #04-01
 Central Mall Office Tower
 Singapore 059567
 +65 6347 6162

CHINA
 KEM flow technology (Beijing) Co., Ltd.
 Rm. 906, Block C, Ruiipu Office Bldg, No. 15
 HongJunYingNan Road
 Chaoyang District, Beijing 100012 | China
 +86 10 84929567



REST OF WORLD
 KEM Küppers Elektromechanik GmbH
 Liebigstraße 5
 85757 Karlsfeld | Germany
 +49 8131 59391-100