### **Industrial Touch Display, Aladdin Family**

# ALAD-181T/(P)

#### 18.5" TFT LCD, Capacitive Touch Screen, HDMI&VGA, OSD Function Keys



#### **Key Features**

- Aluminum die-casting chassis, natural smooth design
- 18.5" TFT LCD, LED backlight
- Projected capacitive screen, support multi touch
- Flat bezel, IP65 Front and IP41 Backside (Vesa mounting)
- HDMI and VGA video input
- Audio input,2\*3W speakers
- DC 9-36V wide power input











ALAD-181T/(P) is a brand new industrial display which support Multi-Touch, with both digital and analog input. It features a 18.5 inches multimedia TFT LCD(1366\*768) with capacitive touch screen. Its functional interfaces match JHCTECH's box computers' and panel PCs' display port. With DC 9-36V wide power input, it is suitable for intelligent manufacturing and Kiosk.




#### **SPEC**

SPEC				
Video		Resolution	1366*768	
	HDMI	Horizontal Frequency	30~90KHz	
		Vertical Frequency	56~75Hz	
	VGA	General		
Audio	Frequency Response	±3dB		
	R/L Channel Separation	70dB		
	Degree of Distortion(THD)	1.5~2%		
	Signal-Noise Ratio(S/N)	80dB		
Power	Input Voltage	DC 9~36V		
	Power Consumption	12V@1.7A(No consumption output)		
	Power Requirement	>12V@2,5A		
	Standby Current	Low power consumption, standby consumption<1W		
Audio Amplifier	$2*3W(4\Omega)$ (Optional)			
OSD Language	Chinese, English, German, French, Russian, Italian, Spanish, Arabic, and so on			
OSD Function Key	AUTO/Power/Menu/Sou	AUTO/Power/Menu/Source/UP(LEFT)/DOWN(RIGHT)		
LED Light	Green for display, red fo	Green for display, red for standby		
	Construction	Aluminum die-casting front bezel and chassis, fin-shaped radiator shell		
Mechanical & Environmental	IP rate	IP65 Front and IP41 Backside (Vesa mounting)		
	Operating Temperature	0~50 with airflow		
	Storage Temperature	-20~60 ° C		
	Storage Humidty	$10{\sim}95\%@40{^\circ}\mathrm{C}$ , non-condensing		
	Shock	10g peak acceleration(duration 11ms)		
	Vibration	1g 5~500Hz		
	Mounting	Panel mounting, VESA 75*75/	100*100mm	
Dimonoron			n; mounting cut out(W*H):473.8*295.8mm	
	Net Weight	6.6.kg		
	EMC	CE, FCC Class A		

	Туре	18.5" TFT LED		
	Resolution	1366*768		
	Color	16.7M colors		
LCD	Pixel Pitch(mm)	0.300*0.3000		
	Brightness(cd/m)	300		
	Viewing Angle	89 Degree(left), 89 Degree(right), 85 Degree(up), 85 Degree(down)		
	Operating Temperature	-0~60℃		
	Backlight Lifetime	50,000 hours		
	Туре	5 wire resistive touch	Projected capacitive touch	
	Resolution	gapless	gapless	
Touch	Light Transmittance	83%	90%	
	Interface	USB/RS232	USB /RS232	
	Consumption	+5V @ 200mA	+ 5V @ 300mA	
	OS	Windows/Linux	Windows/Linux	
	Click Lifetime	35 million times	3 billion times	

Dimension Unit:mm



## **Ordering Info**

NO.	Introductions	
ALAD-181T(P)/ S001-G	Industrial touch display, 18.5" TFT LCD, Projected capacitive touch,1*HDMI, 1*VGA, 1*Audio In, DC 9~36V	
PA-60DC12	AC/DC adapter, DC12V/5A 60W	