

IPC-320

Compact Size Tower IPC with 12th / 13th Gen Intel® Core™ i CPU Socket (LGA 1700) and 250W PSU

NEW




Features

- Intel® 12th / 13th generation Core™ i9/i7/i5/i3 & Pentium®/Celeron® processor with H610E chipset
- Design for operator IPC and application with space limit
- Dual USB 3.2 and dual USB 2.0 port on both front and rear side
- Dual Independent Display (HDMI/ DP)
- 2 low profile Expansion slots (PCIe x16 and PCIe x4)
- Built in with 250W 12V and 5V output only single power supply
- Qualified for Amazon Web Service(AWS) IoT Greengrass



Specifications

13th Generation Processors	CPU	i9-13900(E)	i9-13900TE	i7-13700(E)	i7-13700T(E)	i5-13500(E)	i5-13500T(E)	i5-13400(E)	i3-13100(E)	i3-13100T(E)				
	P-core Base Frequency (Up to)	2.0 GHz	1.1 GHz	2.1 GHz	1.4 GHz	2.5 GHz	1.6 GHz	2.5 GHz	3.4 GHz	2.5 GHz				
	L3 Cache	36 MB	36 MB	30 MB	30 MB	24 MB	24 MB	20MB	12 MB	12 MB				
	Cores	24	24	16	16	14	14	10	4	4				
	Processor Base Power	65 W	35 W	65 W	35 W	65 W	35 W	65W	60 W	35 W				
12th Generation Processor	CPU	i9-12900(E)	i9-12900TE	i7-12700(E)	i7-12700TE	i5-12500(E)	i5-12400	i5-12500TE	i3-12100(E)	i3-12100TE	Pentium G7400E	Pentium G7400TE	Celeron G6900E	Celeron G6900TE
	Base Frequency	2.4GHz	2.3GHz	2.1 GHz	1.4 GHz	2.9 GHz	2.5GHz	1.9 GHz	3.2 GHz	2.1 GHz	3.6 GHz	3.0 GHz	3.0 GHz	2.4 GHz
	L3 Cache	30MB	30MB	25MB	25MB	18 MB	18 MB	18 MB	12 MB	12 MB	6 MB	6 MB	4 MB	4 MB
	Cores	16	16	12	12	6	6	6	4	4	2	2	2	2
	TDP	65W	35W	65W	35W	65W	35W	35W	65W	35W	46W	35W	46W	35W
	Socket	LGA 1700												
	Temperature	0 - 40 °C												
	Chipset	H610E												
	BIOS	AMI 256MB SPI Flash												
	Expansion slot	PCIeX4 (Gen 3)	1											
	PCIeX16 (Gen 4)	1												
Memory	Technology	Dual Channel (Non-ECC) DDR4 3200 MHz												
	Max Capacity	64 GB												
	Sockets	2 x 288-pin DIMM												
Graphics	Controller	Chipset integrated Intel HD Graphics												
	VRAM	Shares system memory is subjected to OS												
Ethernet	Interface	10/100/1000/2.5G Mbps (2.5G for LAN2 only)												
	Controller	GbE LAN1: Intel I219-V; GbE LAN2: Intel I226-V												
	Connector	2 x RJ-45												
SATA	Max. Data Transfer Rate	600 MB/s												
	Channel	3												
Front Panel I/O and Miscellaneous	USB	4 (2 x USB 3.2 Gen1 and 2 x USB 2.0)												
	LED Indicators	PWR, HDD												
Rear I/O	HDMI	1 (Resolution up to 4096 x 2160 @ 60Hz)												
	DP 1.2	1 (Resolution up to 4096 x 2304 @ 60Hz)												
	Ethernet	2												
	USB	4 (2 x USB 3.2 Gen 1, 2 x USB 2.0)												
	Audio	2 (Line-out , Mic-in)												
Internal connectors	USB type A	1												
	SATA	3												
	M.2	M key(link x2)												
	mSATA	1												
Drive bay	Slim Optical Drive	1												
	3.5"	1 (For single 2.5" or 3.5" HDD/SSD, no need 989K008734 bracket) (For dual T: 9.6mm 2.5" HDD/SSD, order 989K008734 bracket)												
Cooling	Fan	NA (Optional as 98R)												
	Air filter	NA (Optional as 98R)												
Environment	Temperature	Operating 0 - 40 °C								Non-Operating -20 ~ 60 °C				
	Humidity	85% RH@ 40 °C, non-condensing												
	Vibration (5-500Hz)	1 Grms												
	Shock	10G (with 11ms duration, hal sine wave)												
	System security monitoring	Chassis intrusion switch (Optional) Padlock hoop Kensington cable lock slot												
Physical Characteristics	Dimension (W x H x D)	95 x 270 x 300 mm (3.74 x 10.63 x 11.81 inch)												
	Weight	3.306 kg (7.289 lb)												
EMC Emission Class		EMI class B												




Front View



- Slim ODD opening
- Power on/off switch
- LED indicators (PWR / HDD)
- USB 2.0 x 2
- USB 3.2 x 2

Rear View



- Dual displays (DP and HDMI)
- USB 2.0 x 2
- USB 3.2 x 2
- Line-out, Mic-in
- Low profile expansion slots (PCIe x16 and PCIe x4)
- 250W 12V and 5Vsb output single power supply
- Dual LAN
- Kensington cable lock slot
- Padlock hoop

Inside View



- Intrusion switch (optional)
- AIMB-308, Intel 12th gen proprietary motherboard
- Drive bay for 3.5" HDDx1 or 2.5" HDDx1*Note1

*Note 1 : Choose convert bracket 989K008734 to have 2x2.5" HDD installed.

Ordering Information

Part number	Compatible motherboard	Compatible CPU cooler	HDD / SSD bay	Power supply wattage					
IPC-320-25A	AIMB-308H-00A1	1970005380T001	1 x 3.5" or 2 x 2.5" (T:9.6 mm)	250W					
Part number	Chipset	PCIex16	PCIex4	SATA	GbE	USB 3.2	USB 2.0	mSATA	M.2
AIMB-308H-00A1	H610E	1	1	3	2	2 (front) 2 (rear)	2 (front) 2 (rear) 1 (internal type A)	1	M key (link x 2)

Packing List

IPC-320

Item	Description	Qty
IPC-320	Compact tower computer chassis	1
	Screws	one bag
1960005359T005	Mounting bracket	a pair
1700018785-11	SATA power cable for storage	1
96PS-A250WFXB12	250W (12V and 5Vsb output only)single power supply	1

AIMB-308H

Item	Description	Qty
AIMB-308	AIMB-308H proprietary motherboard	1
2041030800	Start up Manual for AIMB-308	1
1700018971	SATA data cable 15 cm	1

Optional Accessories

Part number	Description
1970005380T001	CPU blower cooler LGA1700-65W for IPC-320
98R13200001	Fan kit (including 8 cm fan, fan cable, fan filter, fan guard, screws)
1700018785-11	SATA power cable 35cm for storage
1700023646-01	SATA power cable 30cm for Slim ODD
989K008734	Convert frame bracket to fix two 2.5" HDDs/SSDs in a 3.5" drive space
1700033647-01	Intrusion switch (Case open) cable

* Note : Use recommend CPU blower for stable system thermal efficiency

* Note : Always order 98R13200001(Fan kit) with installed add-on card application.