





KAL1224CD

Part number: KAL1224CD

Switching power supply with integrated charger 12Vdc 2A



APPLICATION FIELDS

-  RESIDENTIAL
-  COMMERCIAL
-  MEDICAL
-  PUBLIC SERVICE
-  PUBLIC ENTERTAINMENT

Installation	DIN rail
Format	home
Technology	Switching
Phase	Single
Input voltage (Vac)	100 - 240 Vac
Input current lout (A)	0,45 / 0,35
Inrush current (A)	35

To provide the best possible service, we use cookies on this site. By continuing the navigation you consent to use them. [Read more.](#)

This site use cookies profiling to send you advertising based on your preferences, to know more or remove consent [click here.](#)

OK, CONTINUE X

Input frequency (Hz)	50 - 60
Power Dissipation at 230Vac (W)	11
Efficiency (%)	
Power (W)	25
Output voltage	12 Vdc
Adjustable Output (Vdc)	12 - 14 (only on 12Vdc output)
Output current (A)	2, 1
Working temperature (°C)	-15 +60
Cooling	Natural
Derating	50mA / °C from 40°C to 60°C
IP rating	IP20
Available contact	-
Communication	-
Signalling	Absent output voltage, Charger fault
Protections	Overload, Short circuit, Thermal
Connection	Screw
Material	Plastic fire-retardant UL-94V-0
Standards	EN 61000-3-3, EN 61000-6-1, EN 61000-6-3, EN 62368-1
Classification Pelv / Selv	pelv / selv
Warranty	2 Year
Package quantity (pieces)	1
Height (mm)	90
Width (mm)	70
Depth (mm)	66
Weight (Kg)	0,35

To provide the best possible service, we use cookies on this site. By continuing the navigation you consent to use them. [Read more.](#)

This site use cookies profiling to send you advertising based on your preferences, to know more or remove consent [click here.](#)

OK, CONTINUE X