

KAL2405DIN

Part number: A10100W2

Switching modular power supply 24Vdc 4,5A. 108W



APPLICATION FIELDS



RESIDENTIAL



COMMERCIAL

Installation	DIN rail
Format	home
Technology	Switching
Phase	Single
Input voltage (Vac)	100 - 240 Vac
Input current lout (A)	1,5 (115Vac) / 0,9 (230Vac)
Inrush current (A)	60
Input frequency (Hz)	50
Power Dissipation at 230Vac (W)	14
Power (W)	108

To provide the best possible service, we use cookies on this site. By continuing the navigation you consent to use them. [Read more.](#)

This site uses cookies profiling to send you advertising based on your preferences, to know more or remove consent [click here.](#)

Output voltage	24 Vdc
Adjustable Output (Vdc)	23 - 28
Output current (A)	4,5
Working temperature (°C)	-20 +60
Cooling	Natural
Derating	-
IP rating	IP20
Available contact	-
Communication	-
Signalling	DC OK
Protections	Overload, Short circuit, Thermal
Connection	Screw
Material	Plastic fire-retardant UL-94V-0
Standards	EN 61000-3-3, EN 61000-6-1, EN 61000-6-3, EN 62368-1
Classification Pelv / Selv	pelv / selv
Warranty	2 Year
Package quantity (pieces)	5
Height (mm)	90
Width (mm)	124
Depth (mm)	66
Weight (Kg)	0,35

To provide the best possible service, we use cookies on this site. By continuing the navigation you consent to use them. [Read more.](#)

This site use cookies profiling to send you advertising based on your preferences, to know more or remove consent [click here.](#)

OK, CONTINUE X