






KAL2406DIN

Part number: KAL2406DIN

Switching industrial power supply 24Vdc 7A. 168W



APPLICATION FIELDS

-  COMMERCIAL
-  MEDICAL
-  PUBLIC SERVICE
-  PUBLIC ENTERTAINMENT
-  INDUSTRY

Installation	DIN rail
Format	Industrial
Technology	Switching
Phase	Single
Input voltage (Vac)	100 - 240 Vac
Input current lout (A)	2,4 (115Vac) / 1,5 (230Vac)
Inrush current (A)	80

To provide the best possible service, we use cookies on this site. By continuing the navigation you consent to use them. [Read more.](#)

This site use cookies profiling to send you advertising based on your preferences, to know more or remove consent [click here.](#)

OK, CONTINUE X

Input frequency (Hz)	50 - 60
Power Dissipation at 230Vac (W)	23
Efficiency (%)	>80
Power (W)	168
Output voltage	24 Vdc
Adjustable Output (Vdc)	20 - 28
Output current (A)	7
Working temperature (°C)	-20 +60
Cooling	Natural
Derating	-
IP rating	IP20
Parallel connection	No
Communication	-
Available contact	Contact for functioning
Signalling	DC OK
Protections	Overload, Short circuit, Thermal
Connection	Screw
Material	Alluminum
Standards	EN 61000-3-3, EN 61000-6-1, EN 61000-6-3, EN 62368-1
Classification Pelv / Selv	pelv / selv
Warranty	2 Year
Package quantity (pieces)	4
Height (mm)	111
Width (mm)	75
Depth (mm)	123
Weight (Kg)	0,6

To provide the best possible service, we use cookies on this site. By continuing the navigation you consent to use them. [Read more](#).

This site use cookies profiling to send you advertising based on your preferences, to know more or remove consent [click here](#).

OK, CONTINUE X